imageCLASS MF9280Cdn WORKHORSE PLUS RANGE - Multifunction Laser Printer

This is the ideal solution for corporate and business workgroups. Give your word added impact with beautiful colour images, bold graphics, and sharp text with powerful SEND functionality and auto duplexing.

This intelligent colour multifunction laser offers professional colour output with zero warm up time, so there is no waiting around. The MF9280Cdn will allow you to benefit from superior colour printing,

faxing, copying and scanning in one stylish, cost cutting and space saving unit. It allows you to give your marketing materials added impact with beautiful colour images, bold graphics and sharp text. The imageCLASS MF9280Cdn allows you to scan your documents quickly

and easily for direct distribution via email, network file server, FTP server, internet fax or USB key. The 3.5 inch colour TFT display with easy-scroll wheel allows easy access to all the features.

Key Features

All-in-One cartridges Toner Cartridges

The MF9280Cdn utilises a drum cartridge in which an "Intermediate Transfer Unit", "Photosensitive Drum", and "Waste Toner Container" that are normally individual consumables, are all combined, meaning less consumables to stock and less fuss.

Low Power Consumption and Quick Start Up

By adopting Canon's unique On-Demand Fixing System, there is zero warm up time, so no waiting. The unit springs into action the moment it's needed and with up to 21ppm colour print or copy speeds. The MF9280Cdn is also energy star certified and consumes only 1.2 watts of power in sleep mode, so you not only save on your electricity bill but also the environment too.

As a Laser Printer

- Up to 21 pages per minute for colour and mono
- . 600 x 600 dpi laser print resolution (enhanced to 2400 x 600 dpi by smoothing technology).
- 768MB Memory
- Auto duplex for easy double sided printing and copying
- 3.5" colour TFT display with easy scroll wheel giving you access to all functions.
- PCL & PostScript compatibility

As a Fax Machine

- 33.6 Kbps Super G3 fax up to 3 seconds per page3 fax transmission.
- Huge fax memory of up to 1000 pages to ensure there are no lost messages.
- 50-page Automatic Document Feeder for fast, unattended copying and faxing.


As a Scanner

Up to 600 x 1200 dpi (optical) and 9600 x 9600 dpi (interpolated) colour scanning resolution for sharp images

As a Copier

- 17 copies per minute makes up to 99 copies at a time
- Reduction/enlargement ranges of 50% to 200%; Electronic collating; reserve copy.
- **Laser Printers**

Canon laser printers combine a range of features and technologies to deliver fast, high quality and reliable printing. So, if you are looking to create professional business documents while reducing your running costs, Canon lasers fit the bill.



'anon

advanced simplicity®

Workhorse Plus



Quality images High print resolution (22 ppm, 600 x 600 dpi / up to 1200 x 600 dpi enhanced) @ 21 ppm

High Quality Copying Laser copy quality 600 x 600 dpi @ 21 cpm 600x600dpi



Auto duplex for copy & print Auto duplex for easy double sided printing and copying







Integrated network for workgroup printing


Automatic Document Feeder 50-page Automatic Document Feeder (ADF) for fast unattended copying and faxing.

Fax Memory

Quality Scanning

Huge fax memory of up to 1000 pages to ensure there are no lost messages





Easy Maintenance All-in-one cartridge system meaning only 1 consumable to stock



PCL & PostScript compatibility Fits easily within an established printing solution within an organisation



imageCLASS MF9280Cdn WORKHORSE PLUS RANGE - Multifunction Laser Printer



| Madal | | |
|---|---|--|
| Model Copy Type | MF9280Cdn Colour Laser | |
| Copy Type Copy Speed | Black/Colour : 21/21cpm (A4), 22/22cpm (letter) | |
| Copy Resolution | 600 x 600 dpi | |
| Halftones | 256 Levels | |
| Warm up Time | Less than 60 sec | |
| First Copy Time | Approx. 12.5sec/12.5sec (Black/Colour) | |
| First Print Time | | |
| Paper Source(s) | 250-sheet cassette plus 100-sheet multipurpose tray | |
| Optional Cassette | Optional 500-sheet cassette pedestal | For reliability and continued |
| Paper Weight | 60 to 120 g/m2(cassette), 60 to 176g/m2(multipurpose tray) 250 sheets (face down) | smooth running of your |
| Paper Output Duplex Copy / Bind Type | Yes, 1 to 2, 2 to 1, 2 to 2 /Book, Calender | Canon laser – use genuine |
| Reduce/Enlargement | 50%, 70%, 81%, 86% / 115%, 122%, 141%, 200% (AB system) | Canon Toner |
| Zoom | 50 - 200% in 1% increments | |
| Document Feeder | 50-Sheet | |
| Copy Size | Platen : Up to 8.5" x 14" / 215.9 x 355.6mm | |
| Copy Size | ADF: 5.5" x 5" to 8.5" x 14" / 139.7 x 128mm to 215.9 x 355.6mm | CART317bk |
| Copy Features | ACS(Auto Colour Select), Frame Erase, Memory Sort, | Canon |
| | Toner Save, 2 on 1, 4 on 1 768MB (Shared) | Color Laser Cartridge GENUINE |
| Copy Memory | Printer Specification | |
| Printer Type | Colour Laser | |
| Print Speed | Black/Colour : 21/21cpm (A4), 22/22cpm (letter) | 2 2 317 markets to the line of |
| Print Language | PS, PCL5c/6, UFR II LT(Host Based) | weeded being |
| Print Resolution | 600 x 600 dpi, 2400 x 600 dpi quality (9600 dpi x 600 dpi) | CARTOIT |
| Duplex Print | Yes | CART317c |
| Print Memory | 768MB (Shared) | Color Laser Cartridge GENUINE |
| | Scanner Specification | That for the shart of finiting |
| Scan Type | Colour CCD | |
| Scan Resolution Colour Depth | 600 x 600 dpi (optical) 24-bit | ······································ |
| Document Size | ADF: 5.5" x 5" to 8.5" x 14" / 139.7 x 128mm to 215.9 x 355.6mm | More a control to the magnification and the second larger |
| Duplex Scan | ADF: 5.5 x 5 10 6.5 x 14 / 139.7 x 12611111 10 2 15.9 x 555.61111 Yes | |
| Compatibility | TWAIN, WIA | CART317m |
| Output File Format | JPEG, TIFF | |
| PullScan | | Comon Color Laser Cartridge GENUINE |
| Scan To PC | | multiteritie meet of hooling |
| 0 | Send Specification | |
| Scan to E-Mail | Yes | ······································ |
| Internet Fax Other Protocol | Yes SMB. FTP | Terina arrestos terina Imager2.430 arrestos terina |
| File Format | Hi-compression PDF, PDF, JPEG, TIFF | |
| | Scan To Media Specification | CART317y |
| Scan to USB | | Cana |
| File Format | | Color Laser Cartridge GENUINE |
| | FAX/PC Specification | |
| Modem Speed | Up to 33.6 Kbps | |
| Fax Resolution | Up to 406 x 391 dpi | (iii) 20 Cartodys IIIII |
| Memory Capacity | | - 1. 317 - |
| | Up to 1,000 pages | ana trans 317 Setting Strategy Cardina |
| One-touch Dial | | |
| | 200 location | |
| One-touch Dial Speed Dial | | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features | 200 location Yes (transmission/reception) | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® | Mac Drivers available from |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP/2000 | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function Network Protocol | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP/2000 Mac® OS X 10.4.9 & up (*4), Linux(*5) | |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function Network Protocol Operating System | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP/2000 Mac® OS X 10.4.9 & up (*4), Linux(*5) General Specification | www.canon.com.au/en-AU/Supp |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function Network Protocol Operating System | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP/2000 Mac® OS X 10.4.9 & up (*4), Linux(*5) General Specification 3.5 inch colour TFT | www.canon.com.au/en-AU/Supp |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function Network Protocol Operating System | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP/2000 Mac® OS X 10.4.9 & up (*4), Linux(*5) General Specification 3.5 inch colour TFT 546mm(W) x 527mm(D) x 632mm(H) | www.canon.com.au/en-AU/Supp |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function Network Protocol Operating System | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP/2000 Mac® OS X 10.4.9 & up (*4), Linux(*5) General Specification 3.5 inch colour TFT 546mm(W) x 527mm(D) x 632mm(H) 38.5kg (w/o CRG), 43.3kg (w/ CRG) | www.canon.com.au/en-AU/Supp |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function Network Protocol Operating System | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP/2000 Mac® OS X 10.4.9 & up (*4), Linux(*5) General Specification 3.5 inch colour TFT 546mm(W) x 527mm(D) x 632mm(H) 38.5kg (w/o CRG), 43.3kg (w/ CRG) Max : 1210W | www.canon.com.au/en-AU/Suppo |
| One-touch Dial Speed Dial Duplex Fax Receive Mode Fax Features Memory Backup PC Fax Standard Interface(s) USB Function Network Function Network Protocol Operating System LCD Display Dimensions (W x D x H) Weight(w/o CRG, w/CRG) | 200 location Yes (transmission/reception) FAX Only, Manual, Answering, Fax/Tel Auto SW Remote RX, Delayed TX, Dual Access Yes, 1 hour Yes (sending only) Interface/Software USB 2.0, 10/100 Base-T Ethernet (Network), USB Memory slot (x2), Photo card slot Print and PC Fax Print, PC Fax, Scan and Send TCP/IP Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP/2000 Mac® OS X 10.4.9 & up (*4), Linux(*5) General Specification 3.5 inch colour TFT 546mm(W) x 527mm(D) x 632mm(H) 38.5kg (w/o CRG), 43.3kg (w/ CRG) | www.canon.com.au/en-AU/Suppo |

* Toner cartridge yield in accordance with ISO/IEC 19798

canon.com.au